

BDS-515-SM

515 nm Picosecond Pulsed Diode Laser

Small-size OEM Module

40 mm x 40 mm x 110 mm

Free-beam or single-mode fibre output

Pulse width 80 to 150 ps

Pulse repetition rate 50 MHz



CW equivalent power 0.15 to 1.2 mW

Fast on / off / multiplexing capability

All electronics integrated

No external driver unit

Simple +12 V power supply



Designed and manufactured by



Becker & Hickl GmbH
Nahmitzer Damm 30
12277 Berlin, Berlin
Tel. +49 / 30 / 787 56 32
Fax. +49 / 30 / 787 57 34
email: info@becker-hickl.com
www.becker-hickl.com



LASOS Lasertechnik GmbH
Carl-Zeiss-Promenade 10
07745 Jena, Germany
Tel. +49 3641 2944-0
Fax +49 3641 2944-17
info@lasos.com
www.lasos.com

BDS-515-SM

Optical

Repetition Rate	50 MHz
Wavelength	505 nm to 515 nm, typ. 510 nm
Pulse Width (FWHM, at 1 mW power, 50 MHz)	90 ps
Average (CW equivalent) Power	0.1 mW to 1.2 mW, adjustable via control voltage
Beam diameter, free beam	0.7 mm, TEM ₀₀ mode
Polarisation	horizontal
Coupling efficiency into single-mode fibre, typically	40%
Reaction time to 'Laser on/off' signal	1 μ s
Warm-up time for power and pulse shape stabilisation after power on	1 min ¹⁾

Trigger Output

Pulse Amplitude	-1V (peak) into 50 Ω
Pulse Width	5 ns
Leading edge fall time	1 ns
Output Impedance	50 Ω
Connector	SMA
Delay from Trigger to Optical Pulse	< 500 ps
Jitter between Trigger and Optical Pulse	< 10 ps

Control Inputs

Laser ON / Off	TTL / CMOS low
External Power Control	analog input, 0 to + 10V

Power Supply

Power Supply Voltage	+ 9 V to +15 V
Power Supply Current at 12V	200 mA to 350 mA ²⁾

Mechanical Data

Dimensions	40 mm x 40 mm x 110 mm
Mounting holes	four holes for M3 screws
Heat sink requirements	< 2°C / W ³⁾

Maximum Values

Power Supply Voltage	0 V to +15 V
Voltage at 'Laser On/Off' control input	-2 V to +7 V
Voltage at 'Laser Power' control input	-12 V to + 12 V
Ambient Temperature	0 °C to 40 °C ³⁾

1) Operation below 13 °C ambient temperature may result in extended warm-up time.

2) Depends on case temperature due to laser diode cooling. Cooling current changes with case temperature

3) Laser must be mounted on heat sink. Case temperature must remain below 40°C

Related Products

BDS-SM picosecond diode lasers, 375nm, 405nm, 445nm, 473nm, 488nm, 640nm

BDL-SMC picosecond and CW diode lasers, 375nm, 504nm, 445nm, 473nm, 488nm, 515nm, 640nm



Caution: Class 3B laser product. Avoid direct eye exposure. Light emitted by the device may be harmful to the human eye. Please obey laser safety rules when operating the devices. Complies with US federal laser product performance standards.

International Sales Representatives



US:
Boston Electronics Corp
tcspc@boselec.com
www.boselec.com



UK:
Photonic Solutions PLC
sales@psplc.com
www.psplc.com



Japan:
Tokyo Instruments Inc.
sales@tokyoinst.co.jp
www.tokyoinst.co.jp



China:
DynaSense Photonics Co. Ltd.
info@dyna-sense.com
www.dyna-sense.com